

## 4.03 PRIMAFLEX SPIRA PP80

Temperature range -20 °C bis 100 °C



### Description

Antistatic, flexible fan hose, spiral hose. Can be used from -20°C to +100°C. Made of antistatic PVC-coated polyester fabric and outside with a spring steel spiral incorporated under a scratch protection. Handcrafted with special know-how quality product made of high-quality raw material.

Excellent for conveying gaseous media in areas where static charging is to be avoided. Ideal for ventilation and ventilation of buildings, ships, etc.

Available in our online shop

### Properties

- Insulated
- Lightweight
- Flexible
- High tensile strength
- Non-kinking
- Compressible
- With scuff protection
- Large diameters available
- Continuous connection possible
- Spiral-free sleeves

### Application ranges

Ventilation, Ventilation, Smoke suction, Antistatic hoses, Sewer system air supply and ventilation, Air-conditioning and ventilation technology, Fan hose, Ventilation technology, Mobile suction systems, PVC hoses, Weld fume suction, Tank ventilation, Tank degassing, Shipyards

### Length

Standard length: 7,6 m. Other length on request.

### Further informations

Color: yellow-black.

Extras: end rings instead of end sleeves, Velcro closure for continuous installation..

# TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Spiral spacing (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
102	50	68	0,6	0,05	0,45	7,6	4022102
127	75	87	0,6	0,05	0,56	7,6	4022127
152	75	106	0,6	0,05	0,67	7,6	4022152
203	150	142	0,55	0,05	0,9	7,6	4022203
254	150	178	0,45	0,03	1,18	7,6	4022254
305	150	214	0,35	0,03	1,4	7,6	4022305
356	150	249	0,3	0,03	1,6	7,6	4022356
407	150	285	0,25	0,03	1,8	7,6	4022407
457	150	320	0,22	0,03	2,1	7,6	4022457
508	150	350	0,2	0,025	2,36	7,6	4022508
525	150	368	0,2	0,025	2,47	7,6	4022525
600	150	420	0,17	0,02	2,7	7,6	4022600