

3.02 PRIMAFLEX UNI E13 S

Temperature range -40 °C to 130 °C



Description

Vibration-resistant hose with EPDM (thermoplastic) coated polyester fabric with a spring steel spiral embedded in the wall. Hose can be used in a wide range of applications, particularly suitable for hot and cold air as well as gaseous and liquid media. Universal use in medium temperature range.

Available in our online shop

Properties

- Superior heat resistance
- Vibration-resistant
- Flexible
- Largely smooth interior
- Very lightweight
- Non-kinking
- Good oil and gasoline resistance
- Good resistance to leach and acids
- Good UV resistance and ozone resistance
- Good chemical resistance
- Smallest bending radii

Application ranges

Plant engineering, Supply air hoses, Elastic hose, highly, Vehicle construction, Filter engine, connecting hose, Feed air intake, car, Cold-flexible hoses, Engine fresh air intake, Air-conditioning and ventilation technology, TPE hoses, , Hot air

Länge

Standard length: 10 m.

Sonstige Informationen

Wall thickness: 0.4 mm.

Color: black.

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
40	40	0,35	0,15	0,160	10	6091040
50	50	0,35	0,1	0,210	10	6091050
60	60	0,35	0,08	0,250	10	6091060
70	70	0,3	0,08	0,290	10	6091070
75	75	0,2	0,07	0,310	10	6091075
80	80	0,2	0,06	0,330	10	6091080
100	100	0,15	0,05	0,560	10	6091100
125	125	0,13	0,04	0,700	10	6091125
150	150	0,11	0,04	0,780	10	6091150
175	175	0,09	0,03	0,820	10	6091175
200	200	0,08	0,02	1,270	10	6091200
250	250	0,07	0,02	1,450	10	6091250
300	300	0,05	0,01	1,550	10	6091300
350	350	0,04	0,01	1,600	10	6091350
400	400	0,04	0,01	1,780	10	6091400
450	450	0,03	0,01	2,000	10	6091450
500	500	0,03	0,01	2,250	10	6091500